



MATERIAL SAFETY DATA SHEET

1. Chemical Product and Company Identification

Identification of the preparation C9462A

Manufacturer information Hewlett-Packard Company
1000 NE Circle Boulevard
Corvallis, OR 97330-4239 US

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209
(Direct) 1-503-494-7199

General information telephone number

HP Customer Care Line 1-800-474-6836
(Toll-free) 1-800-474-6836
(Direct) 1-208-323-2551

Date prepared Apr 17, 2007

MSDS number 227941

2. Composition / Information on Ingredients

Component/Substance	CAS Number	% By Weight
Light cyan ink		
Water	7732-18-5	> 70
2-pyrrolidone	616-45-5	< 7.5
Alkyldiol	Proprietary	< 7.5
Diethylene glycol	111-46-6	< 5
Polymer 683-K salt		< 2.5
Light magenta ink		
Water	7732-18-5	> 70
2-pyrrolidone	616-45-5	< 7.5
Alkyldiol	Proprietary	< 7.5
Diethylene glycol	111-46-6	< 5
Polymer 683-K salt		< 2.5

Composition comments This ink supply contains an aqueous ink formulation.
This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Communication Standard).

3. Hazards Identification

Emergency overview Contact with skin and eyes may result in irritation. Ingestion may result in nausea, vomiting and diarrhea.

Acute health effects Any potential hazards are presumed to be due to exposure to the components.

Skin contact

2-pyrrolidone
Contact with skin may result in irritation.

Alkyldiol
Contact with skin may result in irritation.

Polymer 683-K salt
Contact with skin may result in irritation.

Trade Secret blue colorant
Contact with skin may result in irritation.



MATERIAL SAFETY DATA SHEET

Eye contact

2-pyrrolidone
Contact with eyes may result in irritation.

Alkyldiol
Contact with eyes may result in irritation.

Polymer 683-K salt
Contact with eyes may result in irritation.

Trade Secret blue colorant
Contact with eyes may result in irritation.

Inhalation

2-pyrrolidone
Inhalation may result in respiratory irritation.

Alkyldiol
Inhalation may result in respiratory irritation.

Ingestion

2-pyrrolidone
Ingestion may result in nausea, vomiting and diarrhea.

Diethylene glycol
Harmful if swallowed. May cause kidney and liver damage. May depress the central nervous system.

Polymer 683-K salt
Swallowing large amounts may cause digestive discomfort. Ingestion may result in nausea, vomiting and diarrhea.

Potential health effects

Routes of exposure

Potential routes of overexposure to this product are skin and eye contact

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.

Complete toxicity data are not available for this specific formulation

Chronic health effects

None known.

Carcinogenicity

None of the components present in this formulation at concentrations equal to or greater than 0.1% are listed by EU, MAK, IARC, NTP or OSHA.

4. First Aid Measures

First aid procedures

Skin

Wash affected areas thoroughly with mild soap and water. If irritation persists get medical attention.

Eye

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Inhalation

Move to fresh air. If symptoms persist, get medical attention.

Ingestion

If ingestion of a large amount does occur, seek medical attention.

5. Fire Fighting Measures

Flash point and method

> 200 °F (> 93.3 °C); Pensky-Martens Closed Cup

Auto ignition temperature

Not determined



MATERIAL SAFETY DATA SHEET

Hazardous combustion products	Refer to section 10.
Extinguishing media	CO ₂ , water, dry chemical, or foam
Unsuitable extinguishing media	None known.
Unusual fire and explosion hazard	Combustion generates toxic fumes of fluorides/fluorine compounds; aldehydes; ketones.
Special firefighting procedures	None established.

6. Accidental Release Measures

Personal precautions	Wear appropriate personal protective equipment.
Environmental precautions	Do not let product enter drains. Do not flush into surface water or sanitary sewer system.
Procedures if material is released or spilled	Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or other sealed container. Dispose of in compliance with federal, state, and local regulations. See also section 13 Disposal considerations.

7. Handling and Storage

Handling	Avoid contact with skin, eyes and clothing.
Storage	Keep out of the reach of children. Keep away from excessive heat or cold. Store away from strong oxidizers.

8. Exposure Controls/Personal Protection

Exposure limit values	Exposure limits have not been established for this product.
Personal protective equipment	
General	Use personal protective equipment to minimize exposure to skin and eye.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.
Exposure guidelines	Use in a well ventilated area.

9. Physical & Chemical Properties

pH	9.2
Vapor pressure	Not determined
Boiling point	Not determined
Solubility	Soluble in water
Specific gravity	1 - 1.1
Flash point	> 200 °F (> 93.3 °C)
Vapor density	> 1 (air = 1.0)
Evaporation rate	Not determined
Flammability	Not determined
Oxidizing properties	Not determined
Color	magenta/cyan

10. Chemical Stability & Reactivity Information

Stability	Stable under recommended storage conditions.
Hazardous polymerization	Will not occur.



MATERIAL SAFETY DATA SHEET

Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons., hydrogen fluoride, fluorinated hydrocarbons, aldehydes, ketones
Incompatibility	Incompatible with strong bases and oxidizing agents.

11. Toxicological Information

This ink formulation has not been tested for toxicological effects.
Refer to Section 3 for potential health effects and Section 4 for first aid measures.

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Light cyan ink
LC50/96h/Fathead minnows => 750 mg/l
Light magenta ink
LC50/96h/Fathead minnows => 750 mg/L

13. Disposal Considerations

Disposal instructions Dispose of in compliance with federal, state, and local regulations. HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit <http://www.hp.com/recycle>.

14. Transportation Information

General Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.

IATA

Proper shipping name	Not applicable
Hazard class	Not applicable
Packaging exceptions	none
Identification number (UN)	None
Packing group	N/A

15. Regulatory Information

International regulations All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

US federal regulations US TSCA 12(b): Does not contain listed chemicals.

HMIS ratings

Health:	1
Flammability:	2
Physical hazard:	0

NFPA ratings

Health:	1
Flammability:	2
Instability:	0

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes



MATERIAL SAFETY DATA SHEET

Hazard categories
Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).

Issue date Apr 17 2007 12:18PM

Revision 1

Replaces sheet dated Aug 17 2006 10:57AM

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act

VOC Volatile Organic Compounds