# **TOSHIBA**

# **MATERIAL SAFETY DATA SHEET**

Date of Preparation : April 25, 2011 MSDS: T1910U1W Date of Revised : Page 1 of 6

## SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name : Toner for Process Cartridge T-1910
Used for : Toshiba facsimile, e-STUDIO 191F

Company Name : Toshiba TEC Corporation

Address : 2-17-2, Higashigotanda, Shinagawa-ku, Tokyo, 141-8664, Japan

Telephone Number : +81-3-6422-7700

Contact : (1) Toshiba America Business Solutions, Inc.

Emergency Telephone. No. : +1-800-424-9300

For calls within the U.S. only.

(2) Toshiba of Canada Limited

Telephone. No. : +1-905-470-3500

For calls within Canada only.

## SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT(S)              | CAS No.   | <u>wt.%</u> |
|----------------------------|-----------|-------------|
| Styrene acrylate copolymer |           | >88.0       |
| Carbon Black               | 1333-86-4 | <5.0        |
| Amorphous Silica           |           | <3.0        |
| Polypropylene              |           | <2.0        |
| Organic pigment            |           | <1.0        |

--- TRADE SECRET

#### SECTION 3 HAZARDS IDENTIFICATION

Emergency Overview : If used as intended, the product does not present acute or chronic

health hazard.

Physical Hazards : This product is not classified as flammable or combustible.

It will burn in case of fire.

Avoid contact with strong oxidizers such as chromate, bromate and nitrates.

Routes of Exposure : Inhalation, dermal contact, incidental ingestion

Product Identity : Toner for Process Cartridge T-1910 MSDS: T1910U1W

Page 2 of 6

Inhalation : Excessive inhalation may cause irritation of the nose,

throat and respiratory tract.

Eye Contact : Non-irritant.

Dermal Contact : Non-irritant, non-sensitiser.

Ingestion : Not currently known.

Fire and Explosion

Sensitivity to Mechanical Impact

: None

Sensitivity t Static Charge: None

#### SECTION 4 FIRST AID MEASURES

Eye Contact : Immediately flush eyes with plenty of water for at least 15 minutes.

If irritation persists, call a physician.

Skin Contact : Wash with soap and water. Wash clothing before reuse.

If irritation occurs or is persistent, seek medical attention.

Ingestion : Dilute stomach contents with several glasses of water.

Inhalation : Remove from exposure area to fresh air immediately.

Contact a physician if there is any difficulty in breathing or other signs of distress.

#### SECTION 5 FIRE FIGHTING MEASURES

General Hazard : Product will burn in case of fire.

Flash Point : Not applicable
Flammable Limits : Not applicable
Autoignition Temperature : Not applicable
Flammability classification : Not applicable

Unusual Fire & Explosion Hazard

: Combustible powder. Dust of this product at sufficient concentrations can form explosive mixtures with air.

**Hazardous Combustion Products** 

: Carbon monoxide, carbon dioxide and smoke.

Extinguishing Media : Foam, halon, carbon dioxide, dry chemical & water fog. Fire-Fighting Equipment : Wear full bunker gear including a positive pressure

self-contained breathing apparatus in case of burning in large quantities.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

Spills or Leaks : Vacuum-clean spilled toner and carefully transfer into sealable waste

container. If no vacuum-cleaner is available, sweep slowly to minimize generation of dust during clean-up. Residue can be removed with soap

and cold water.

Product Identity: Toner for Process Cartridge T-1910 MSDS: T1910U1W Page 3 of 6

SECTION 7 HANDLING AND STORAGE

Handling : Avoid dust, keep away from ignition sources.

Prevention of Fire and Explosion

: This material is capable of creating a dust explosion.

Keep away from heat, sparks & flame.

Storage : Keep container in cool and dry area.

Hygienic Practices : Avoid inhalation and ingestion. Avoid getting in eyes, on skin or clothing.

Wash hands thoroughly after handling, and before eating, drinking,

or smoking.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits** 

OSHA PELs (TWA)

as the product : 15mg/m³ (Total dust)

5mg/m<sup>3</sup> (Respirable fraction)

Carbon black : 3.5 mg/m<sup>3</sup>
Other substances : Not listed

ACGIH TLVs (TWA)

as the product : 10mg/m³ (Total dust)

3mg/m<sup>3</sup> (Respirable fraction)

Carbon black : 3.5 mg/m<sup>3</sup>
Other substances : Not listed

DFG-MAK (TWA)

as the product : 4mg/m³ (Inhalable fraction)

1.5mg/m<sup>3</sup> (Respirable fraction)

All substances : Not listed

NOHSC (TWA)

All substances : Not listed

Engineering Controls : Maintain adequate ventilation.

Eye Protection : Not required under intended use.

Skin Protection : Not required under intended use.

Respiratory Protection : Not required under intended use.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Fine solid powder

Odor : Odorless
Boiling Point : Not applicable
Vapor Pressure : Not applicable
Vapor Density : Not applicable
Solubility (H<sub>2</sub>O) : Negligible
Specific Gravity : Ca. 1.10 g/cm3
Melting Point : Not applicable

pH Value : Not a water-based product, therefore not applicable.

Percent Volatile : Not applicable

Product Identity : Toner for Process Cartridge T-1910 MSDS : T1910U1W

Page 4 of 6

#### SECTION 10 STABILITY AND REACTIVITY

Stability : Stable

Incompatibility : Not identified.

Hazardous Decomposition Products

: Carbon monoxide and carbon dioxide.

Hazardous Polymerization: : Will not occur.

#### SECTION 11 SUPPLEMENTAL HEALTH INFORMATION

Mutagenicity : Negative in the Ames test.

Carcinogenicity: : In 1996, the IARC classified carbon black as a Group 2B carcinogen

(possible human carcinogen).

Chronic Effects: : In a study in rats by chronic inhalation exposure to a typical toner, a mild

to moderate degree of lung fibrosis was observed in 92 % of the rats in the high concentration (16 mg/m³)exposure group, and a minimal to mild degree of fibrosis was noted in 22% of the animals in the middle (4

mg/m<sup>3</sup>) exposure group. These findings are attributed to "lung overloading", a general response to excessive amounts of any dust

retained in the lungs for a prolonged period.

## SECTION 12 ECOLOGICAL INFORMATION

Aquatic environmennt : LC50-No Data available (fish)

: EC50-No Data available (daphnia): EbC50-No Data available (Algal)

#### SECTION 13 DISPOSAL CONSIDERATION

Dispose of in accordance with local, state and federal regulation.

Empty plastic container may be recycled.

## SECTION 14 TRANSPORTATION INFORMATION

Special Precautions : None International Transport Information

UN Classification Number : Not applicable

Land DOT 49 CFR, ADR: Not classified as Dangeous Goods
Sea IMDG Code: Not classified as Dangeous Goods
Air ICAO-TI: Not classified as Dangeous Goods

Product Identity: Toner for Process Cartridge T-1910 MSDS: T1910U1W Page 5 of 6

## SECTION 15 REGULATORY INFORMATION

IARC : See section 11.

**US/Canada Information** 

OSHA Hazard Communication Standard, 29CFR 1910. 1200

: Not regulated.

Toxic Substance Control Act (TSCA)

: All chemical substances in this product comply with

all applicable rules or orders under TSCA.

RCRA (40 CFR 261) : Product or components not listed.

CERCLA/SARA Information: Not regulated.

NTP Annual Report on Carcinogens

: Not listed as an NTP carcinogen.

California Proposition 65 : Neither toner, or any of the components, are listed as chemicals known

to the State of California to cause cancer or reproductive system effects.

Controlled Products Regulations(Canada)

: This product has been classified in accordance with the hazard criteria

of the CPR.

Workplace Hazardous Materials Information System(Canada)

: No toxicology information available

Other State Regulations : Carbon black is listed in the New Jersey Right to Know List,

Pennsylvania Hazardous Substance List, and Massachusetts Substance List.

U.S./Canada Label Statements

: LOW HAZARD FOR RECOMMENDED HANDLING. Minimize dust

generation and accumulation. Use with adequate ventilation.

### SECTION 16 OTHER INFORMATION

National Fire Protection Association (NFPA) Classification:

Flammability : 1
Reactivity : 0
Health : 1

(0 = insignificant, 1 = slight)

Hazardous Materials Information Systems (HMIS):

Red (Flammability) : 1
Yellow (Reactivity) : 0
Blue (Acute Effects) : 1

(0 = insignificant, 1 = slight)

#### **Product Identity**

: Toner for Process Cartridge T-1910

Page 6 of 6

MSDS: T1910U1W

#### Notice

: Judgments as to the suitability of information herein for purchaser's purposes are necessarily purchaser's responsibility.

Therefore, although reasonable care has been taken in the preparation of such information, Toshiba Corporation extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.

#### References

: IARC (1996) IARC Monographs on the Evaluation of the Carcinogenic Risks of Chemicals to Humans, Vol. 65, Printing Processes and Printing Inks, Carbon Black and Some Nitro Compounds, Lyon, pp. 149-261.

H. Muhle, B. Bellmann, O. Creutzenberg, C. Dasenbrock, H. Ernst, R. Kilpper, J. C. MacKenzie, P. Morrow, U. Mohr,

S. Takenaka, and R. Mermelstein (1991).

Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats, Fundamental and Applied Toxicology 17, pp. 280-299.

#### Abbreviation

- : (1) OSHA PEL stands for Permissible Exposure Limit under Occupational Safety and Health Administration (USA).
  - (2) ACGIH TLV stands for Threshold Limit Value under American Conference of Governmental Industrial Hygienists (USA).
  - (3) DFG-MAK stands for Maximale Arbeitsplatzkonzentrationen under Deutsche Forschungsgemeinschaft.
  - (4) TWA stands for Time Weighted Average.
  - (5) IARC stands for International Agency for Research on Cancer.
  - (6) NTP stands for National Toxicology Program (USA).
  - (7) NIOSH stands for National Institute for Occupational Safety and Health (USA).
  - (8) DOT stands for Department of Transportation (USA).
  - (9) NOHSC stands for National Occupational Heath and Safety Commission (Australia).